



Totally Focused. Totally Independent.

Technical Specification

ECP32 2 C



The world's largest
independent producer of
alternators 1 – 5,000kVA

Standards

Alternators are designed and produced within an ISO 9001 environment. The entire series is manufactured according to, and complies with, the most common specifications such as CEI 2-3, IEC 34-1, EN 60034-1, VDE 0530, BS 4999-5000, NF 51.111, NEMA MG 1-2011, ISO 8528-3. They also comply with other specific standards such as UL1446, UL 1004/4 and /B and CAN/CSA-C22.2 No14-95-No100-95.

Windings and Performances

All windings are 2/3rds pitch to eliminate triplen harmonics within the voltage waveform and to avoid excessive neutral currents in certain parallel operating conditions. A fully interconnected aluminium or copper damper cage is supplied on the rotor of all models (excluding the ECP3 series).


- ▶ 12 wire reconnectable:
50Hz – 380V to 440V and 220/110V to 240/120V (de-rates may apply at certain voltages)
60Hz – 380V to 480V and 220/110V to 240/120V (de-rates may apply at certain voltages)
- ▶ 6 wire reconnectable:
50Hz – 380V to 440V and 220V to 240V (de-rates may apply at certain voltages)
60Hz – 380V to 480V and 220V to 240V (de-rates may apply at certain voltages)

Winding Configurations	Standard		Special (dedicated)			
	12 wire Reconnectable	6 wire Reconnectable	380V and 600V 60Hz	690V 50/60Hz	220-240V 1ph 50Hz	220-240V 1ph 60Hz
ECP3 to ECO38	Std	Option	Option	Option	Option	Option
ECO40 to ECO46	Std	Option	Option	Option	Option (to ECO40)	
ECO47	Std 4 wires		Option	Option		
Insulation materials	Class H	Class H	Class H	Class H	Class H	Class H
High efficiency	Std	Std	Std	Std	Std	Std
High motor starting	>300%	>300%	>300%	>300%	>300%	>300%
THD (Total Harmonic Distortion)	Typically <3.5% full load L-L	Typically <3.0% full load L-L	Typically <3.5% full load L-L	Typically <3.5% full load L-L	Typically <4.5% full load L-N	Typically <4.5% full load L-N
Interference suppression	VDE 0875 G/N/K, EN61000-6-3, EN61000-6-2, others available on request					

Winding Protection

There are various degrees of protection for the windings following the standard impregnation process, as can be seen here. The TOTAL+ butadienic black flexible coating is recommended for arduous applications.

Winding Protection:	STANDARD	STANDARD+	GREY	GREY+	TOTAL+
ECP3	Std	Option	Option	Option	Option
ECP28 and ECP32	-	Std	Option	Option	Option
NPE32, ECP34 to ECO47	-	-	Std	Option	Option



Grey treatment (marinization) on the left, TOTAL+ treatment shown on the right. The EG43 grey varnish, is an high temperature insulating enamel that forms a tough and flexible film, with excellent moisture and chemical protection. It is water and oil proof, and also protects windings from abrasion. It is applied spraying an over coating layer over the impregnated winding, or dipping the stator in a varnish barrel for superior treatments.


The TOTAL+ is a Mecc Alte protection system. It is the ultimate winding treatment that offers truly superior performances when the environment is really harsh, or the application very demanding. The TOTAL+ is also extremely resistant to the particle abrasion as it adsorbs the impacts.

Design


The robust mechanical structure withstands up to 5G in any direction and 9G vertically and its design permits easy access to the connections and components during routine maintenance check-ups. The mechanical design has used the most advanced FEM analysis. The materials used are: DD12 steel for the frame, C45 steel for the shaft and cast iron or aluminum pressure die cast for the end-brackets: fans are either aluminum die casted or nylon fiber glass loaded, UL compliant materials. Rotors are dynamically balanced according grades 6.3 (up to series 32) or 2.5 (from series 34 onwards) of ISO 1940-1.

Terminals and Terminal Box

Easy access to regulators is assured through a pull out drawer or a drop down panel to allow safer adjustment. Large terminal boxes allow easy access of power cables, in the ECO43 and ECO46 higher power ranges the terminal allow the convenient choice of power cable or busbar connection with versatility of entry and connection. Current transformers are available as an option on series ECO 40, 43, 46 and 47 with single or dual output.




On C type family has been installed a new AVR panel. Terminal boards have been redesigned into a special L configuration, specifically to ease customer wiring; with this kind of terminal board it is possible to place a second terminal board in order to get 12 available terminals. Current transformers are available as an option on series ECO38 with single or dual output.



Ingress Protection

In addition to the protection on the windings themselves, alternators can increase the protection on the inlet side. Standard level is IP23 but the following solutions are also available: IP23 DP with inlet filters, IP23 with only terminal box in IP45, IP43 and IP45. Derates may be applied.



Info: https://www.meccalte.com/downloads/MA0605_Bulletin_IP.pdf

Excitation and Regulation Systems

All ECP/ECO series have MAUX auxiliary winding to power the digital regulator. Both DSR and the DER1 are available to connect to PC through the DxR2 USB interface and DxR TERMINAL software to interrogate/download alarms & settings for analysis or for cloning other regulators. DER2 has got an integrated USB connection and can be connected to the PC without any optional connection boards. More settings such as LAMS, digital RAM based synchronous external control and soft start are obtainable through the DxR connection. Simple analogue potentiometers are available for the more usual adjustments.

Excitation Systems	DSR	DER1	DER2
ECP3 to ECO38	Std	Option	Option
ECO40 to ECO46	-	Std	Option
ECO47	-	-	Std
Parallel Operation	√	√	√
Mains Parallel	√	√	√
3 Phase Sensing (rms)	-	√	√
Accuracy	+/-1%	+/-0.5%	+/-0.5%
Remote Voltage Control	√	√	√
Alarm Log	√	√	√
Analogue and Digital Configurable	√	√	√
LAMS (Load Acceptance V/f)	√	√	√
APO (Active Protection Output)	√	√	√
Soft Start	√	√	√
High dynamic response	-	-	√
USB connection without external boards	-	-	√

For a given motor start duty a smaller generator may be selected – as it has lower subtransient reactance values for non-linear loads. The whole range from 6.5 to 3400kVA is capable of >300% sustained short circuit current for up to 20 seconds.


Optional PMG

The Mecc Alte PMG is available on ECP28, ECP30, ECP32, ECP34 and ECO38 as factory-fitted option; alternatively, only the predisposition for the retrofit, for subsequent assembly, is available on option.

On ECO 40, 43 and 46 series it is available as a factory-fitted or retro-fitted options.


For ECO47 PMG is standard.

The complete AVR range is fully compatible with both MAUX and PMG systems, this minimises spare part management and flexibility of stock as one AVR suits all applications. The PMG is delivering the same amount of kVA available with the MAUX.



Dew Heater

Our entire range can be equipped with anti-condensation resistors of adequate power and sized for the alternator. Voltage for heaters must be specified when ordering. New cylindrical cartridge style heaters are available on request and it can be retrofitted.



Accessories

Additional optionals can be fit on our alternator series, such as PTC thermistors or PT100 both on windings and bearings, dew heaters, high and low profile of terminal boxes (on most series), parallel devices, current and voltage transformers, air filters, IP43 and IP45 protections and many others.

For more info visit: <https://www.meccalte.com/en/products/alternators/accessories/c-type-accessories>

Deration coefficients

Altitude (meters)	Ambient temperature (Celsius)							
	25	40	45	50	55	60	65	70
≤ 1000	1.07	1	0.96	0.93	0.91	0.89	0.85	0.82
$> 1000 \leq 1500$	1.01	0.96	0.92	0.89	0.87	0.84	0.81	0.77
$> 1500 \leq 2000$	0.96	0.91	0.87	0.84	0.83	0.79	0.77	0.73
$> 2000 \leq 3000$	0.90	0.85	0.81	0.78	0.76	0.73	0.71	0.68
$> 3000 \leq 4000$	0.84	0.78	0.75	0.73	0.70	0.68	0.66	0.62
$> 4000 \leq 5000$	0.78	0.72	0.69	0.67	0.65	0.62	0.59	0.56
$> 5000 \leq 6000$	0.70	0.65	0.63	0.61	0.58	0.55	0.53	0.50

Notes on short circuit curves

The indicated coefficients have to be used to correct the three phase short circuit curves values as a function of the rated voltage.

The indicated coefficient have to be used to correct the three phase short circuit curves values as a function of the type of short circuit voltage.

50 Hz		60 Hz			3 phase	2 phase L-L	1 phase L-N
Voltage	Factor	Voltage	Factor				
380	0.93X	415	0.85X	<i>Istantaneous</i>	1X	0.87X	1.30X
400	1X	440	0.90X	<i>Minimum</i>	1X	1.80X	3.20X
415	1.04X	460	0.95X	<i>Sustained</i>	1X	1.50X	2.50X
440	1.10X	480	1X	<i>Max Duration</i>	20 sec.	10 sec.	4 sec.

All the curves are shown for series or parallel star connection at 400V 50 Hz or 480V 60 Hz. If the unit is reconnected from series to parallel star, the additional coefficient is 2X. From series star to series delta, it is 1.72X. From series star to parallel delta, it is 3.44X.

General characteristics

Pole number	2	Insulation class	H
Phase number	3	Protection class	IP23
Number of wires	12	NDE Bearing type	6309-2RS
Execution	Brushless	DE Bearing type	6312-2RS
Regulator type	DSR	Maximum Overspeed	4320
Winding pitch	2/3	Altitude	0-1000
Code voltage reference	T0405S3	Balancing	ISO1940-1

Ratings 50Hz

kVA / kW @ Temp. Rise / Ambient °C - 0.8 PF		STANDBY-163/27				STANDBY-150/40				H-125/40				F-105/40				B-80/40			
Series		380V	400V	415V	440V	380V	400V	415V	440V	380V	400V	415V	440V	380V	400V	415V	440V	380V	400V	415V	440V
Parallel Star YY		190V	200V	208V	220V	190V	200V	208V	220V	190V	200V	208V	220V	190V	200V	208V	220V	190V	200V	208V	220V
Series Delta Δ		220V	230V	240V	254V	220V	230V	240V	254V	220V	230V	240V	254V	220V	230V	240V	254V	220V	230V	240V	254V
Parallel Delta ΔΔ		110V	115V	120V	127V	110V	115V	120V	127V	110V	115V	120V	127V	110V	115V	120V	127V	110V	115V	120V	127V
ECP32 1S2 C	kVA	48	48	48	41,5	46	46	46	39,7	44	44	44	38	40	40	40	34,5	35,2	35,2	35,2	30,4
	kW	38,4	38,4	38,4	33,2	36,8	36,8	36,8	31,8	35,2	35,2	35,2	30,4	32	32	32	27,6	28,2	28,2	28,2	24,3
ECP32 2S2 C	kVA	54	54	54	45,9	52	52	52	44,2	50	50	50	42,5	45	45	45	38,5	40	40	40	34
	kW	43,2	43,2	43,2	36,7	41,6	41,6	41,6	35,4	40	40	40	34	36	36	36	30,8	32	32	32	27,2
ECP32 M2 C	kVA	71	71	70	59,2	69	69	67,5	57,5	66	66	65	55	60	60	59	50	52,8	52,8	52	44
	kW	56,8	56,8	56	47,4	55,2	55,2	54	46	52,8	52,8	52	44	48	48	47,2	40	42,2	42,2	41,6	35,2
ECP32 L2 C	kVA	89	89	87	72,7	85,5	85,5	83,5	69,9	82	82	80	67	75	75	73	61	65,6	65,6	64	53,6
	kW	71,2	71,2	69,6	58,2	68,4	68,4	66,8	55,9	65,6	65,6	64	53,6	60	60	58,4	48,8	52,5	52,5	51,2	42,9

Ratings 60Hz

kVA / kW @ Temp. Rise / Ambient °C - 0.8 PF		STANDBY-163/27				STANDBY-150/40				H-125/40				F-105/40				B-80/40			
Series		415V	440V	460V	480V	415V	440V	460V	480V	415V	440V	460V	480V	415V	440V	460V	480V	415V	440V	460V	480V
Parallel Star YY		208V	220V	230V	240V	208V	220V	230V	240V	208V	220V	230V	240V	208V	220V	230V	240V	208V	220V	230V	240V
Series Delta Δ		240V	254V	265V	277V	240V	254V	265V	277V	240V	254V	265V	277V	240V	254V	265V	277V	240V	254V	265V	277V
Parallel Delta ΔΔ		120V	127V	133V	138V	120V	127V	133V	138V	120V	127V	133V	138V	120V	127V	133V	138V	120V	127V	133V	138V
ECP32 1S2 C	kVA	50,6	58	58	58	48,2	55,5	55,5	55,5	46	51	53	53	41,5	46	48	48	36,8	40,8	42,4	42,4
	kW	40,5	46,4	46,4	46,4	38,6	44,4	44,4	44,4	36,8	40,8	42,4	42,4	33,2	36,8	38,4	38,4	29,4	32,6	33,9	33,9
ECP32 2S2 C	kVA	56,3	62,8	65	65	54,6	60,4	62,5	62,5	52	58	60	60	46,8	52	54	54	41,6	46,4	48	48
	kW	45	50,2	52	52	43,7	48,3	50	50	41,6	46,4	48	48	37,4	41,6	43,2	43,2	33,3	37,1	38,4	38,4
ECP32 M2 C	kVA	72,7	80,2	85	85	71	78,3	83	83	68	75	79,5	79,5	61,5	68	72	72	54,4	60	63,6	63,6
	kW	58,2	64,2	68	68	56,8	62,6	66,4	66,4	54,4	60	63,6	63,6	49,2	54,4	57,6	57,6	43,5	48	50,9	50,9
ECP32 L2 C	kVA	91,2	101,0	107	107	87,6	97,0	102,8	102,8	84	93	98,5	98,5	76	85	90	90	67,2	74,4	78,8	78,8
	kW	73,0	80,8	85,6	85,6	70,1	77,6	82,2	82,2	67,2	74,4	78,8	78,8	60,8	68	72	72	53,8	59,5	63,0	63,0

Reactance & Time constants- Class H / 400V

Unsaturated (ref. EN60034-4)			ECP32 1S2 C	ECP32 2S2 C	ECP32 M2 C	ECP32 L2 C
X_d	Direct-axis synchronous reactance	%	394,3	406,8	431,9	487,9
X'_d	Direct-axis transient reactance	%	12,8	11,5	11,6	11,3
X''_d	Direct-axis subtransient reactance	%	6,58	5,6	5,72	5,13
X_q	Quadrature-axis synchronous reactance	%	221,2	216,5	222,7	242,3
X'_q	Quadrature-axis transient reactance	%	221,2	216,5	222,7	242,3
X''_q	Quadrature-axis subtransient reactance	%	26,6	23,3	26,8	18,7
X₂	Negative-sequence reactance	%	16	13,9	15,7	11,3
X₀	Zero sequence reactance	%	2,81	2,95	2,49	2,65
Saturated						
X_d	Direct-axis synchronous reactance	%	335,2	345,8	367,1	414,7
X'_d	Direct-axis transient reactance	%	10,9	9,78	9,86	9,6
X''_d	Direct-axis subtransient reactance	%	5,59	4,76	4,86	4,36
X_q	Quadrature-axis synchronous reactance	%	188	184	189,3	206
X'_q	Quadrature-axis transient reactance	%	188	184	189,3	206
X''_q	Quadrature-axis subtransient reactance	%	22,6	19,8	22,8	15,9
X₂	Negative-sequence reactance	%	13,6	11,8	13,3	9,6
X₀	Zero sequence reactance	%	2,81	2,95	2,49	2,65
K_{cc}	Short circuit ratio		0,3	0,29	0,27	0,24
T'_d	Transient time constant	sec	0,069	0,072	0,074	0,075
T''_d	Subtransient time constant	sec	0,016	0,013	0,017	0,016
T'_{do}	Open circuit time constant	sec	1,1	1,3	1,2	1,4
T_a	Armature time constant	sec	0,015	0,011	0,009	0,016

Additional information - Class H / 400V

I_o	Excitation current at no load	A	0,7	0,7	0,6	0,7
I_c	Excitation current at full load	A	2,7	2,7	2,1	2,4
Overload						
Overload per 10 sec.		%	300			
Heat dissipation		W	5167	5403	6929	7943
Telephone Harmonic Factor - THF		%	<2	<2	<2	<2
Waveform Distors.(THD) full load LL/LN		%	4,4 / 3,9	4,3 / 4	4,4 / 3,9	4,5 / 4
Waveform Distors.(THD) no load LL/LN		%	3,7 / 3,3	3,6 / 3,2	3,5 / 3,2	3,3 / 2,9

Reactance & Time constants- Class H / 480V





Unsaturated (ref. EN60034-4)			ECP32 1S2 C	ECP32 2S2 C	ECP32 M2 C	ECP32 L2 C
X_d	Direct-axis synchronous reactance	%	395,8	406,8	433,5	488,4
X'_d	Direct-axis transient reactance	%	12,8	11,5	11,6	11,3
X''_d	Direct-axis subtransient reactance	%	6,6	5,6	5,74	5,14
X_q	Quadrature-axis synchronous reactance	%	222	216,5	223,5	242,5
X'_q	Quadrature-axis transient reactance	%	222	216,5	223,5	242,5
X''_q	Quadrature-axis subtransient reactance	%	26,7	23,3	26,9	18,7
X₂	Negative-sequence reactance	%	16,1	13,9	15,8	11,3
X₀	Zero sequence reactance	%	2,82	2,95	2,5	2,65
Saturated						
X_d	Direct-axis synchronous reactance	%	336,4	345,8	368,5	415,1
X'_d	Direct-axis transient reactance	%	10,9	9,78	9,86	9,6
X''_d	Direct-axis subtransient reactance	%	5,61	4,76	4,88	4,37
X_q	Quadrature-axis synchronous reactance	%	188,7	184	190	206,1
X'_q	Quadrature-axis transient reactance	%	188,7	184	190	206,1
X''_q	Quadrature-axis subtransient reactance	%	22,7	19,8	22,9	15,9
X₂	Negative-sequence reactance	%	13,7	11,8	13,4	9,6
X₀	Zero sequence reactance	%	2,82	2,95	2,5	2,65
K_{cc}	Short circuit ratio		0,3	0,29	0,27	0,24
T'_d	Transient time constant	sec	0,069	0,072	0,074	0,075
T''_d	Subtransient time constant	sec	0,016	0,013	0,017	0,016
T'_{do}	Open circuit time constant	sec	1,1	1,3	1,2	1,4
T_a	Armature time constant	sec	0,015	0,011	0,009	0,016

Additional information - Class H / 480V

I_o	Excitation current at no load	A	0,7	0,7	0,6	0,7
I_c	Excitation current at full load	A	2,7	2,7	2,1	2,4
Overload						
Overload per 10 sec.		%	300			
Heat dissipation		W	5240	5631	6910	8176
Telephone Interference Factor - TIF			<50	<50	<50	<50
Waveform Distors.(THD) full load LL/LN		%	4,4 / 3,9	4,3 / 4	4,4 / 3,9	4,5 / 4
Waveform Distors.(THD) no load LL/LN		%	3,7 / 3,3	3,6 / 3,2	3,5 / 3,2	3,3 / 2,9





Efficiencies @ 50Hz

Models		380V 50Hz					400V 50Hz					415V 50Hz					440V 50Hz				
		0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1
ECP32 1S2 C	%	84,4	86,4	87,3	87,5	87,2	84,6	86,3	87,6	87,2	86,9	84,8	86,3	87,7	87,5	87,2	85,3	86,8	88,0	87,7	87,4
ECP32 2S2 C	%	83,0	85,3	88,6	88,4	87,8	82,2	85,4	88,5	88,1	87,5	83,4	85,4	88,6	88,5	87,9	83,2	85,7	88,9	88,6	88,0
ECP32 M2 C	%	81,8	85,6	88,7	88,7	88,0	82,0	85,5	88,6	88,4	87,7	82,2	85,5	88,7	88,7	88,0	82,7	85,8	89,0	88,9	88,2
ECP32 L2 C	%	82,0	86,6	89,5	89,3	88,9	82,2	86,7	89,7	89,2	88,8	82,0	86,5	89,3	88,7	88,3	82,5	86,8	89,6	88,9	88,5




Efficiencies @ 60Hz

Models		415V 60Hz					440V 60Hz					460V 60Hz					480V 60Hz				
		0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1	0.25	0.5	0.75	1	1.1
ECP32 1S2 C	%	86,0	88,8	89,7	89,1	88,8	86,2	88,8	89,7	89,8	89,4	86,0	88,7	89,5	89,0	88,7	86,0	88,7	89,5	89,0	88,7
ECP32 2S2 C	%	84,2	86,9	89,9	89,6	89,0	84,4	86,9	89,6	89,3	88,7	83,9	86,7	89,8	89,6	89,0	84,2	86,8	89,7	89,5	88,9
ECP32 M2 C	%	83,1	86,4	90,6	90,3	89,7	83,3	86,4	90,3	90,0	89,4	82,8	86,2	90,5	90,3	89,7	83,1	86,3	90,4	90,2	89,6
ECP32 L2 C	%	83,3	87,3	91,0	90,6	90,2	83,4	87,3	90,7	90,3	89,9	82,9	87,1	90,9	90,6	90,2	83,4	87,5	91,0	90,6	90,2



Transients voltage



In order to scale transient curves as a function of a power factor or voltage if not indicated, please proceed as follows:

Power Factor coefficient corrector (PFCC), to be used on power factor 0.6 curves:

$$PFCC = \sin(\text{ARCCos}(PF_{\text{new}})) / 0.8$$

Example. The PFCC at power factor 0.3 is 1.192 [$PFCC = \sin(\text{ARCCos}(0.3)) / 0.8$]. This means that the voltage fall at a given power at pf 0.3 is equivalent to the one that can be read on the pf 0.6 curve if the load is considered 1.192 times bigger (19% higher value.).

In this example, a 100 kVA load insertion at pf 0.3 is equivalent in voltage fall to a 119kVA load insertion at pf 0.6.

Voltage coefficient corrector (VCC):


$$VCC = (400/V_{\text{new}})^2 \text{ if } 50 \text{ Hz}; VCC = (480/V_{\text{new}})^2 \text{ if } 60 \text{ Hz}$$

Example. VCC at 415V 60 Hz is 1.338 [$VCC = (480/415)^2$]. This means that the voltage fall at a given power at 415V is equivalent to the one that can be read on the power factor 0.6 curve if the load is considered 1.338 times bigger (33% higher value.).


In this example, a 100 kVA load insertion at 415V is equivalent in voltage fall to a 133kVA load insertion at 480V.

50Hz Short circuit decrement curves - No load excitation at rated speed


ECP32 1S2 C




ECP32 2S2 C



ECP32 M2 C




ECP32 L2 C




*Please refer to tables at page 6

60Hz Short circuit decrement curves - No load excitation at rated speed


ECP32 1S2 C




ECP32 2S2 C



ECP32 M2 C



ECP32 L2 C




*Please refer to tables at page 6

Additional Characteristics


Data	ECP32 1S2 C		ECP32 2S2 C		ECP32 M2 C		ECP32 L2 C		
	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz	
Damper cage	Aluminium								
Stator Winding Resistance (20°C)	Ω	0,11	0,064		0,03714		0,02214		
Rotor Winding Resistance (20°C)	Ω	3,65	4,071		4,301		4,68		
Stator Exciter Resistance (20°C)	Ω	10,6	10,6		10,6		10,6		
Rotor Exciter Resistance (20°C)	Ω	0,417	0,417		0,417		0,417		
Weight of complete generator	kg	173,0	199,0		212,0		231,0		
Unbalanced magnetic pull	kN/mm	3,7	3,8		4,0		4,1		
Air flow	m ³ /min	22,4	27,0	22,4	27,0	22,4	27,0	22,4	27,0
Noise level at 1m/7m	dB(A)	88/77	93/80	88/77	93/80	88/77	93/80	88/77	93/80

MOMENTS OF INERTIA - DOUBLE BEARING





COMPONENT	1		2		3		4		TOTAL		DIMENSION	A	B	C
	WEIGHT	J	WEIGHT	J	WEIGHT	J	WEIGHT	J	WEIGHT	J				
ECP32 1S2 C			25,8	0,151			13,7	0,0068	46	0,1864	ECP32 1S2 C	606,4	516,9	336,9
ECP32 2S2 C	1	0,0114	32,8	0,1928	5,5	0,0172	13,7	0,0068	53	0,2282	ECP32 2S2 C	606,4	516,9	329,4
ECP32 M2 C			42,7	0,2525			15,5	0,0077	64,7	0,2888	ECP32 M2 C	676,4	586,9	374,4
ECP32 L2 C			52,7	0,3122			17	0,0085	76,2	0,3493	ECP32 L2 C	736,4	641,9	399,4
ECP32 1S4 C			33,8	0,2268			13,7	0,0068	54	0,2622	ECP32 1S4 C	606,4	516,9	339,4
ECP32 2S4 C	1	0,0114	38,3	0,2567	5,5	0,0172	13,7	0,0068	58,5	0,2921	ECP32 2S4 C	606,4	516,9	329,4
ECP32 1M4 C			44,1	0,2955			15,5	0,0077	66,1	0,3318	ECP32 1M4 C	676,4	586,9	386,9
ECP32 2M4 C			54,3	0,3629			15,5	0,0077	76,3	0,3992	ECP32 2M4 C	676,4	586,9	364,4
ECP32 1L4 C			63,3	0,4225			17	0,0085	86,8	0,4596	ECP32 1L4 C	736,4	641,9	394,4
ECP32 2L4 C			65,7	0,4387			17	0,0085	89,2	0,4758	ECP32 2L4 C	736,4	641,9	389,4

B0746_01_ECP32C_B3B14




SERIE	MODELLO	A	B	I	L.E.	C.G.
ECP32C/2 B3B14	1S	535,5	118	167	255,7	
	2S	535,5	118	167	251,6	
	M	605,5	243	196	293,6	
	L	665,5	336	256	321,3	
ECP32C/4 B3B14	1S	651	535,5	118	167	257,1
	2S	651	535,5	118	167	252,0
	M	721	605,5	243	196	300,8
	2M	721	605,5	243	196	288,1
	1L	781	665,5	336	256	318,8
	2L	781	665,5	336	256	315,7



- COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI
REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS
- PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE
REMOVABLE PANEL FOR ACCESS TO AVR
- FORD STANDARD PER INGRESSO CAVI Ø60mm
STANDARD HOLE FOR CABLE ENTRY Ø60mm
- PRE-TAGLIO SU PANNELLO PRINCIPALE PER INGRESSO CAVI Ø60mm
PRE-CUT ON MAIN PANEL FOR CABLE ENTRY Ø60mm
- PRE-TAGLIO SU PANNELLO LATERALE PER INGRESSO CAVI Ø28mm
PRE-CUT ON LATERAL PANEL FOR CABLE ENTRY Ø28mm
- VITE M6 PER MESSA A TERRA
SCREW M6 FOR GROUNDING

B0765_03_ECP32C_B3B14

MOMENTS OF INERTIA - SINGLE BEARING




POS. COMPONENT	1 FAN		2 MAIN ROTOR		3 EXCITER ROTOR		4 SHAFT		TOTAL	
	WEIGHT [kg]	J [kgm ²]	WEIGHT [kg]	J [kgm ²]	WEIGHT [kg]	J [kgm ²]	WEIGHT [kg]	J [kgm ²]	WEIGHT [kg]	J [kgm ²]
ECP32 1S2 C	1	0,0114	25,8	0,151	5,5	0,0172	13,4	0,0068	45,7	0,1864
ECP32 2S2 C			32,8	0,1928			13,4	0,0068	52,7	0,2282
ECP32 M2 C			42,7	0,2525			15,2	0,0078	64,4	0,2889
ECP32 L2 C			52,7	0,3122			16,7	0,0086	75,9	0,3494
ECP32 1S4 C	1	0,0114	33,8	0,2268	5,5	0,0172	13,4	0,0068	53,7	0,2622
ECP32 2S4 C			38,3	0,2567			13,4	0,0068	58,2	0,2921
ECP32 1M4 C			44,1	0,2955			15,2	0,0078	65,8	0,3319
ECP32 2M4 C			54,3	0,3629			15,2	0,0078	76	0,3993
ECP32 1L4 C			63,3	0,4225			16,7	0,0086	86,5	0,4597
ECP32 2L4 C			65,7	0,4387			16,7	0,0086	88,9	0,4759

TYPE	A	B	C
ECP32 1S2 C	581	475,5	295,5
ECP32 2S2 C	581	475,5	288
ECP32 M2 C	651	545,5	333
ECP32 L2 C	711	600,5	358
ECP32 1S4 C	581	475,5	298
ECP32 2S4 C	581	475,5	288
ECP32 1M4 C	651	545,5	345,5
ECP32 2M4 C	651	545,5	323
ECP32 1L4 C	711	600,5	353
ECP32 2L4 C	711	600,5	348

SAE N°	D	E	WEIGHT [kg]	J [kgm ²]
6 1/2	5	2,2	1,7	0,0084
7 1/2	5	2,2	2,1	0,0130
8	36,6	25,9	4	0,0203
10	28,6	21,6	4,5	0,0385
11 1/2	15	11,5	4,5	0,0590

80740_01_ECP32C_MD35



SERIE	MODELLO	A	B	I	L.E.	C.G.
ECP32C/2	1S	551,5	200	183	288,7	
	2S	551,5	200	183	282,1	
	M	621,5	325	212	324,4	
	L	681,5	418	272	351,4	

FLANGIA/FLANGE BRIDE/FLANSCH						
SAE N.	O	P	Q	α	N	
5	356	314,3	333,4	45°	8	
4	402	362,0	381,0	30°	12	
3	453	409,6	428,6	30°	12	
2	490	447,7	466,7	30°	12	
1	553	512	530,2	30°	12	

GIUNTI A DISCHI / DISC COUPLING DISQUE DE MONOPALIER / SCHEIBENKUPPLUNG						
SAE N.	g	L	g1	S1	g11	N1
6 1/2	215,90	30,2	200,00	9	60°	6
7 1/2	241,30	30,2	222,25	9	45°	8
8	263,52	62,0	244,47	11	60°	6
10	314,32	53,8	295,27	11	45°	8
11 1/2	352,42	39,6	333,37	11	45°	8

- COPERCHIO REMOVIBILE PER ACCESSO AI TERMINALI PRINCIPALI
REMOVABLE COVER FOR ACCESS TO MAIN TERMINALS
- PANNELLO REMOVIBILE PER ACCESSO AL REGOLATORE
REMOVABLE PANEL FOR ACCESS TO AIR
- FORO STANDARD PER INGRESSO CAVI #60mm
STANDARD HOLE FOR CABLE ENTRY #60mm
- PRE-TAGLIO SU PANNELLO PRINCIPALE PER INGRESSO CAVI #60mm
PRE-CUT ON MAIN PANEL FOR CABLE ENTRY #60mm
- PRE-TAGLIO SU PANNELLO LATERALE PER INGRESSO CAVI #28mm
PRE-CUT ON LATERAL PANEL FOR CABLE ENTRY #28mm
- VITE M6 PER MESSA A TERRA
SCREW M6 FOR GROUNDING
- CENTRO DI GRAVITA' IN CONFIGURAZIONE SAE 3 FLYWHEEL 115
GRAVITY CENTER IN CONFIGURATION SAE 3 FLYWHEEL 115

80764_04_ECP32C_MD35

Notes

Mecc Alte SpA (HQ)

Via Roma
20 - 36051 Creazzo
Vicenza - ITALY
T: +39 0444 396111
E: info@meccalte.it
aftersales@meccalte.it

Mecc Alte Portable

Via Roma
20 - 36051 Creazzo
Vicenza - ITALY
T: +39 0444 396111
E: info@meccalte.it

Mecc Alte Power Products srl

Via Melaro
2 - 36075 Montecchio
Maggiore (VI) - ITALY
T: +39 0444 1831295
E: info@meccalte.it

Zanardi Alternatori srl

Via Dei Laghi
48/B - 36077 Altavilla
Vicenza - ITALY
T: +39 0444 370799
E: info@zanardialternatori.it

United Kingdom

Mecc Alte U.K. LTD
6 Lands' End Way
Oakham
Rutland LE15 6RF
T: +44 (0) 1572 771160
E: info@meccalte.co.uk

Spain

Mecc Alte España S.A.
C/ Rio Taibilla, 2
Polig. Ind. Los Valeros
03178 Benijofar (Alicante)
T: +34 (0) 96 6702152
E: info@meccalte.es

China

Mecc Alte Alternator Haimen LTD
755 Nanghai East Rd
Jiangsu HEDZ 226100 PRC
T: +86 (0) 513 82325758
E: info@meccalte.cn

India

Mecc Alte India PVT LTD
Plot NO: 1, Sanaswadi
Talegaon
Dhamdhare Road Taluka:
Shirur, District:
Pune - 412208
Maharashtra, India
T: +91 2137 619600
E: info@meccalte.in

U.S.A. and Canada

Mecc Alte Inc.
1229 Adams Drive
McHenry, IL, 60051
T: +1 815 344 0530
E: info@meccalte.us

Germany

Mecc Alte Generatoren GmbH
Bucher Hang 2
D-87448 Waltenhofen
T: +49 (0)831 540755 0
E: info@meccalte.de

Australia

Mecc Alte Alternators PTY LTD
10 Duncan Road, PO Box 1046
Dry Creek, 5094, South
Australia
T: +61 (0) 8 8349 8422
E: info@meccalte.com.au

France

Mecc Alte International S.A.
Z.E.La Gagnerie
16330 ST.Amant de Boixe
T: +33 (0) 545 397562
E: info@meccalte.fr

Far East

Mecc Alte (F.E.) PTE LTD
19 Kian Teck Drive
Singapore 628836
T: +65 62 657122
E: info@meccalte.com.sg



www.meccalte.com